

ARMTEX® ATTACK™

Lightweight All-Polyester Double Jacket
Rubber Lined Fire Hose

COLORS:



General Applications:

- Municipal fire departments
- Industrial fire brigades
- Shipboard fire fighting

Construction:

Double-jacket polyester hose with a synthetic EPDM rubber ozone resistant lining.

Abrasion Resistant Jacket – Designed with superior abrasion resistance and kink resistance to resist damage from constant working conditions, even when using low pressure and straight bore nozzles. A smooth waterway surface for lower friction loss. Jacket color options include blue, green, black, orange, purple, red, tan, white and yellow.

Service Temperature Range:

Remains flexible at temperatures as low as -40°F (-40°C).

Features and Advantages:

- High Burst Rating – 1,200 psi up to 3" diameter.
- Superior Performance: Very low friction loss.
- ARMTEX® ATTACK™ is available in the sizes of 1 1/2", 1 3/4", 2", 2 1/2" and 3".
- Packs Tight – KFP's best packing and easiest to fold double-jacket, rubber-lined hose.
- Maintenance Free – Immune to mildew and rot.
- Meets or exceeds National Fire Protection Association (NFPA) 1961 Standard on Fire Hose (current edition).
- 10-year warranty.

Packaging:

Available in 25', 50' and 100' lengths.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

**Lightweight All-Polyester Double Jacket
Rubber Lined Fire Hose**

Nominal Specifications

| Part Number* | Size (in) | Color | Coupling Size (in) | Coupling Type | Bowl Size (in) | Service Test (psi) | Proof Test (psi) | Burst Test (psi) | Available Lengths (ft) | Weight Uncoupled (lbs/ft) |
|-----------------|-----------|--------|--------------------|---------------|----------------|--------------------|------------------|------------------|------------------------|---------------------------|
| AA150BXXX-NH150 | 1 1/2 | Blue | 1 1/2 | NST | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150BXXX-NP150 | 1 1/2 | Blue | 1 1/2 | NPSH | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150GXXX-NH150 | 1 1/2 | Green | 1 1/2 | NST | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150GXXX-NP150 | 1 1/2 | Green | 1 1/2 | NPSH | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150LXXX-NH150 | 1 1/2 | Black | 1 1/2 | NST | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150LXXX-NP150 | 1 1/2 | Black | 1 1/2 | NPSH | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150OXXX-NH150 | 1 1/2 | Orange | 1 1/2 | NST | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150OXXX-NP150 | 1 1/2 | Orange | 1 1/2 | NPSH | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150PXXX-NH150 | 1 1/2 | Purple | 1 1/2 | NST | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150PXXX-NP150 | 1 1/2 | Purple | 1 1/2 | NPSH | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150RXXX-NH150 | 1 1/2 | Red | 1 1/2 | NST | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150RXXX-NP150 | 1 1/2 | Red | 1 1/2 | NPSH | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150TXXX-NH150 | 1 1/2 | Tan | 1 1/2 | NST | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150TXXX-NP150 | 1 1/2 | Tan | 1 1/2 | NPSH | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150WXXX-NH150 | 1 1/2 | White | 1 1/2 | NST | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150WXXX-NP150 | 1 1/2 | White | 1 1/2 | NPSH | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150YXXX-NH150 | 1 1/2 | Yellow | 1 1/2 | NST | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA150YXXX-NP150 | 1 1/2 | Yellow | 1 1/2 | NPSH | 1 15/16 | 400 | 800 | 1200 | 25/50/100 | 0.30 |
| AA175BXXX-NH150 | 1 3/4 | Blue | 1 1/2 | NST | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175BXXX-NP150 | 1 3/4 | Blue | 1 1/2 | NPSH | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175GXXX-NH150 | 1 3/4 | Green | 1 1/2 | NST | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175GXXX-NP150 | 1 3/4 | Green | 1 1/2 | NPSH | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175LXXX-NH150 | 1 3/4 | Black | 1 1/2 | NST | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175LXXX-NP150 | 1 3/4 | Black | 1 1/2 | NPSH | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175OXXX-NH150 | 1 3/4 | Orange | 1 1/2 | NST | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175OXXX-NP150 | 1 3/4 | Orange | 1 1/2 | NPSH | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175PXXX-NH150 | 1 3/4 | Purple | 1 1/2 | NST | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175PXXX-NP150 | 1 3/4 | Purple | 1 1/2 | NPSH | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175RXXX-NH150 | 1 3/4 | Red | 1 1/2 | NST | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175RXXX-NP150 | 1 3/4 | Red | 1 1/2 | NPSH | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175TXXX-NH150 | 1 3/4 | Tan | 1 1/2 | NST | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175TXXX-NP150 | 1 3/4 | Tan | 1 1/2 | NPSH | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |

*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

**Lightweight All-Polyester Double Jacket
Rubber Lined Fire Hose**

Nominal Specifications

| Part Number* | Size (in) | Color | Coupling Size (in) | Coupling Type | Bowl Size (in) | Service Test (psi) | Proof Test (psi) | Burst Test (psi) | Available Lengths (ft) | Weight Uncoupled (lbs/ft) |
|-----------------|-----------|--------|--------------------|---------------|----------------|--------------------|------------------|------------------|------------------------|---------------------------|
| AA175WXXX-NH150 | 1 3/4 | White | 1 1/2 | NST | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175WXXX-NP150 | 1 3/4 | White | 1 1/2 | NPSH | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175YXXX-NH150 | 1 3/4 | Yellow | 1 1/2 | NST | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA175YXXX-NP150 | 1 3/4 | Yellow | 1 1/2 | NPSH | 2 1/8 | 400 | 800 | 1200 | 25/50/100 | 0.34 |
| AA200BXXX-NH150 | 2 | Blue | 1 1/2 | NST | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200BXXX-NP150 | 2 | Blue | 1 1/2 | NPSH | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200GXXX-NH150 | 2 | Green | 1 1/2 | NST | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200GXXX-NP150 | 2 | Green | 1 1/2 | NPSH | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200LXXX-NH150 | 2 | Black | 1 1/2 | NST | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200LXXX-NP150 | 2 | Black | 1 1/2 | NPSH | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200OXXX-NH150 | 2 | Orange | 1 1/2 | NST | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200OXXX-NP150 | 2 | Orange | 1 1/2 | NPSH | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200PXXX-NH150 | 2 | Purple | 1 1/2 | NST | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200PXXX-NP150 | 2 | Purple | 1 1/2 | NPSH | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200RXXX-NH150 | 2 | Red | 1 1/2 | NST | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200RXXX-NP150 | 2 | Red | 1 1/2 | NPSH | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200TXXX-NH150 | 2 | Tan | 1 1/2 | NST | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200TXXX-NP150 | 2 | Tan | 1 1/2 | NPSH | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200WXXX-NH150 | 2 | White | 1 1/2 | NST | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200WXXX-NP150 | 2 | White | 1 1/2 | NPSH | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200YXXX-NH150 | 2 | Yellow | 1 1/2 | NST | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA200YXXX-NP150 | 2 | Yellow | 1 1/2 | NPSH | 2 15/32 | 400 | 800 | 1200 | 25/50/100 | 0.44 |
| AA250BXXX-NH250 | 2 1/2 | Blue | 2 1/2 | NST | 3 | 400 | 800 | 1200 | 25/50/100 | 0.50 |
| AA250GXXX-NH250 | 2 1/2 | Green | 2 1/2 | NST | 3 | 400 | 800 | 1200 | 25/50/100 | 0.50 |
| AA250LXXX-NH250 | 2 1/2 | Black | 2 1/2 | NST | 3 | 400 | 800 | 1200 | 25/50/100 | 0.50 |
| AA250OXXX-NH250 | 2 1/2 | Orange | 2 1/2 | NST | 3 | 400 | 800 | 1200 | 25/50/100 | 0.50 |
| AA250PXXX-NH250 | 2 1/2 | Purple | 2 1/2 | NST | 3 | 400 | 800 | 1200 | 25/50/100 | 0.50 |
| AA250RXXX-NH250 | 2 1/2 | Red | 2 1/2 | NST | 3 | 400 | 800 | 1200 | 25/50/100 | 0.50 |
| AA250TXXX-NH250 | 2 1/2 | Tan | 2 1/2 | NST | 3 | 400 | 800 | 1200 | 25/50/100 | 0.50 |
| AA250WXXX-NH250 | 2 1/2 | White | 2 1/2 | NST | 3 | 400 | 800 | 1200 | 25/50/100 | 0.50 |
| AA250YXXX-NH250 | 2 1/2 | Yellow | 2 1/2 | NST | 3 | 400 | 800 | 1200 | 25/50/100 | 0.50 |
| AA300BXXX-NH250 | 3 | Blue | 2 1/2 | NST | 3 1/2 | 400 | 800 | 1200 | 25/50/100 | 0.62 |

*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

Lightweight All-Polyester Double Jacket Rubber Lined Fire Hose

Nominal Specifications

| Part Number* | Size (in) | Color | Coupling Size (in) | Coupling Type | Bowl Size (in) | Service Test (psi) | Proof Test (psi) | Burst Test (psi) | Available Lengths (ft) | Weight Uncoupled (lbs/ft) |
|-----------------|-----------|--------|--------------------|---------------|----------------|--------------------|------------------|------------------|------------------------|---------------------------|
| AA300GXXX-NH250 | 3 | Green | 2 1/2 | NST | 3 1/2 | 400 | 800 | 1200 | 25/50/100 | 0.62 |
| AA300LXXX-NH250 | 3 | Black | 2 1/2 | NST | 3 1/2 | 400 | 800 | 1200 | 25/50/100 | 0.62 |
| AA300OXXX-NH250 | 3 | Orange | 2 1/2 | NST | 3 1/2 | 400 | 800 | 1200 | 25/50/100 | 0.62 |
| AA300PXXX-NH250 | 3 | Purple | 2 1/2 | NST | 3 1/2 | 400 | 800 | 1200 | 25/50/100 | 0.62 |
| AA300RXXX-NH250 | 3 | Red | 2 1/2 | NST | 3 1/2 | 400 | 800 | 1200 | 25/50/100 | 0.62 |
| AA300TXXX-NH250 | 3 | Tan | 2 1/2 | NST | 3 1/2 | 400 | 800 | 1200 | 25/50/100 | 0.62 |
| AA300WXXX-NH250 | 3 | White | 2 1/2 | NST | 3 1/2 | 400 | 800 | 1200 | 25/50/100 | 0.62 |
| AA300YXXX-NH250 | 3 | Yellow | 2 1/2 | NST | 3 1/2 | 400 | 800 | 1200 | 25/50/100 | 0.62 |

*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.